

NINEK NANOTECH PVT. LTD.

Product Name : 9K TORNADO LOW (Double Density PU/PU)



Detail :

Footwear needs to be appropriate to the occupation, the working environment, and feet protection. Depending upon the safety and workplace requirements one can choose safety shoe with properties and features like water resistance, heat resistance, foot protection, slip resistance, energy absorption etc. The differences between Rubber and Polyurethane are heat and chemical resistance properties. Rubber soles give greater resistance. Shoes with rubber soles are therefore the correct choice for areas of application in which these kinds of hazards

Description :

NAME	9K TORNADO LOW
UPPER MATERIAL	GENUINE LEATHER 1.8-2.0 MM THICKNESS
QUARTER LINING	Sweat absorbent grey/orange mesh.
TOE CAP	Steel Toe Cap EN 12568 200J with Comfort Strip. Protect
	against compression injury up to 15 KN.
INSOLE	Anti-Static Insole.
MIDSOLE	Polyurethane (PU) Black colour serving as a Cushion for
	comfort.
OUTSOLE	Nitrile Rubber having excellent abrasion resistance and
	heat resistant up to 300? C.
INSOCKS	4 mm PU foam Insocks.

SIZE	UK 04 - UK 14
PROPERTIES	Anti-static, ANTI SKID, OIL & ACID RESISTANT, SHOCK
	ABSORBER AND HEAT RESISTANT UP TO 300? C
OPTIONAL	Anti-penetration Kevlar/Steel Midplate, Polycarbonate toe
	cap.