

NINEK NANOTECH PVT. LTD.

Product Name : 9K OXFORD (PU/Rubber)



Detail :

The differences between Rubber and Polyurethane are heat and chemical resistance properties. Rubber soles give greater resistance. Shoes with rubber soles are therefore the correct choice for areas of application in which these kinds of hazards may arise. Vulcanized Nitrile Rubber can withstand temperature of 300° C. PU+Nitrile Rubber shoes provide comfort to the wearer. Polyurethane midsole gives cushioning effect and helps in energy absorption thereby increasing the work efficiency of the wearer. Also, PU+Nitrile Rubber shoes are light

Description :

NAME	9K OXFORD
UPPER MATERIAL	GENUINE LEATHER 1.8-2.0 MM THICKNESS
QUARTER LINING	Sweat absorbent Black Mesh / Goat lining having excellent
	abrasion resistance.
TOE CAP	Polycarbonate Toe Cap EN 12568 200J with Comfort Strip.
	Protect against
compression injury up to 15 KN.	
INSOLE	Anti-Static Insole.
MIDSOLE	Polyurethane (PU) Black colour serving as a Cushion for
	comfort.

OUTSOLE	Nitrile Rubber having excellent abrasion resistance and
	heat resistant up to 300?
C.	
INSOCKS	4 mm Soft EVA socks.
SIZE	UK 03 - UK 12
PROPERTIES	ANTI STATIC, ANTI SKID, OIL & ACID RESISTANT, SHOCK
	ABSORBER AND HEAT
RESISTANT UP TO 300? C	
OPTIONAL	Anti-penetration Kevlar.