## **NINEK NANOTECH PVT. LTD.**





## **Detail:**

The differences between Rubber and Polyurethane are heat and chemical resistance properties. Rubber soles give greater resistance. Shoes with rubber soles are therefore the correct choice for areas of application in which these kinds of hazards may arise. Vulcanized Nitrile Rubber can withstand temperature of 300° C. PU+Nitrile Rubber shoes provide comfort to the wearer. Polyurethane midsole gives cushioning effect and helps in energy absorption thereby increasing the work efficiency of the wearer. Also, PU+Nitrile Rubber shoes are light

## **Description:**

NAME	9K ATLAS BROWN		
UPPER MATERIAL	GENUINE LEATHER 1.8-2.0 MM THICKNESS AND WATER RESISTANT		
QUARTER LINING	Sweat absorbent black mesh having excellent abrasion		
	resistance.		
TOE CAP	Polycarbonate Toe Cap EN 12568 200J with Comfort Strip.		
TOE CAP	Protect against		
compression injury up to 15 KN.			
INSOLE	Anti-Static Penetration resistant Kevlar. Tested for 1100		
MIDSOLE	Newton.		
	Polyurethane (PU) Black colour serving as a Cushion for		
WIIDSOLE	comfort.		

	OUTSOLE	Nitrile Rubber having excellent abrasion resistance and
		heat resistant up to 300?
	C.	
	INSOCKS	6 mm soft PU moulded Insocks.
	SIZE	UK 04 - UK 14
	PROPERTIES	Anti-static, Anti penetration, ANTI SKID, OIL & ACID
		RESISTANT, SHOCK ABSORBER
AND	ND HEAT RESISTANT UP TO 300? C	